

+48 515 322608, +48 606 363000



info@gmlsystem.pl



www.gmlsystem.eu



Cantilever sliding gate with bars infill from galvanized steel (Product RKS-T-ISCHTOR-14-S)


Self-supporting sliding gate from galvanized and powder painted steel with vertical bar infill.

Standard gates for 4-8 m driveway, 1.5 to 2.4 m height.

Roller carriages built into ground track.

Example project






+48 515 322608, +48 606 363000



info@gmlsystem.pl




www.gmlsystem.eu





Technical Details:

1. gate type: cantilever sliding gate, self-supporting,
2. opening width: 4500mm,
3. height: 1400mm,
4. filling: vertical bars with distance between bars about 100mm,
5. gate construction: welded frame from square tube profiles 60x60mm with welded infill bars screwed to ground track 120x100x5mm,
6. material and color: galvanized steel, powder painted, any color from the RAL color palette,



Limanowskiego 6/21, 30-534 Krakow



7. posts: double guiding and double receiver posts from square tube on footplate,
8. accessories: 2 high-quality roller carriages, flashing beacon,
9. automation: electrical drive equipped with remote control, Beninca BULL.

Production time 4-6 weeks

Welded construction. Pre-assembly of the whole construction takes place in workshop.