



+48 515 322608, +48 606 363000



[info@gmlsystem.pl](mailto:info@gmlsystem.pl)



[www.gmlsystem.eu](http://www.gmlsystem.eu)



## **Cantilever sliding gate from galvanized steel with aluminum slats filling** ( Product RKS-T-ISCHTOR-16-S )

Self-supporting sliding gate with slats filling from galvanized steel, powder painted.

Standard gates for 4-8 m driveway, 1.5 to 2.4 m height.

Roller carriages built into ground track.

### **Example project**





*GML System*  
steel-glass constructions

+48 515 322608, +48 606 363000



[info@gmlsystem.pl](mailto:info@gmlsystem.pl)



[www.gmlsystem.eu](http://www.gmlsystem.eu)



### Technical Details:

1. gate type: cantilever sliding gate, self-supporting,
2. opening width: 5900mm,
3. height: 2300mm,
4. filling: filling with horizontal aluminum slats,
5. gate construction: welded frame from profiles 80x80mm and ground track 120x100x5mm,
6. material and color: galvanized steel, powder painted, any color from the RAL color palette,



*GML System*  
*steel-glass constructions*



+48 515 322608, +48 606 363000



[info@gmlsystem.pl](mailto:info@gmlsystem.pl)



[www.gmlsystem.eu](http://www.gmlsystem.eu)

7. posts: single receiver post from square tube profile 80x80mm on footplate, upper guide bracket fixed to a fence wall,
8. accessories: 2 high-quality roller carriages with 12 rolls each, flashing beacon,
9. automation: electrical drive equipped with remote control, Beninca BULL 8.

### **Production time 4-6 weeks**

Welded construction. Pre-assembly of the whole construction takes place in workshop.